

Let's build a website



# Simple blog Images

SEO Letsencrypt

Multilingual

CMS

Simple blog	Search
Images	Access control
SEO	E-mail
Letsencrypt	WebSockets
Multilingual	S <sub>3</sub>
CMS	Caching









django

















CMS web framework

### It's Erlang!

Natural async

Long-lived processes (WebSockets)

Fault tolerance

In-memory caching

Less waste



### And...

Controllerless pages

Dynamic routing

MQTT with UBF

Built-in e-mail

And more...

## Principles

Powerful templates


Aggressive caching


Include batteries

```
<h1>{{ id.title }}</h1>
<l
{% for article in m.search[{query hasobject=[id, 'author']}] %}
    {{ article.title }}
{% endfor %}
```


```
{% live template="user-status.tpl"
       topic="~pagesession/session"
                                         Subscribe to session
       target="user-status" %}
                                         MQTT topic
user-status.tpl:
                        Access check
{% if m.acl.user %}
     Greetings user {{ m.acl.user.name_first }}!
{% else %}
    Hello anonymous! Why not log in so we can better track you?
{% endif %}
```

Small teams, large impact




















## Data vision











-v `pwd`:/opt/zotonic/user/sites \
-p 8443:8443 zotonic/zotonic-heavy

\$ docker run \

```
{% for result in m.search[{recommend hasobject=[id, 'author']}] as results %}
-module(yoursite).
-include_lib("zotonic_core/include/zotonic.hrl").
observe_search_query(#search_query{search = {recommend, Args}} = Query, Context) ->
    recommend:search(Query, Context);
observe_search_query(_, _) ->
    undefined.
                   next observer,
                   based on prio
```

```
-module(yoursite).
-include_lib("zotonic_core/include/zotonic.hrl").
observe acl is allowed(#acl is allowed{action = view, object = Id}, Context) ->
    case m_rsc:is_a(Id, recommendation, Context) of
       true ->
            custom acl:can view recommendation(Id, Context);
       false ->
            undefined
    end;
observe_acl_is_allowed(#acl_is_allowed{}, _Context) ->
    undefined.
                   next observer
```

# 16 releases

And counting...



# 



Semver breaking the bserver'
-[] -> << >>
-17 att check

We changed a lot

Cowboy

Fixed bottlenecks

The Great Binarification

Dispatch Compiler

**Template Compiler** 

## THIS SUMMER



## Some history

2010

2011

2014

2017

Zotonic 0.1.0

2009

NPM

Elixir

Hex

Erlang 20

Zotonic 1.0

Rebar

Erlang R13B03

#### [WIP] Turn Zotonic components into OTP applications

Edit

#1717






ferd commented on Aug 10, 2016


Owner

In fact, I can't publish erlpass to hex because the bcrypt dependencies on there are too old. Can't do it for now.


П



## As application server



### As dependency







## Thanks!

David de Boer @ddeboer\_nl

zotonic.com